

SJE Quest® I and II Pump Floats

Mechanically-activated, wide-angle pump switches provide automatic control of pumps, alarms, and control panels in wastewater and non-potable water applications. Adjustable pumping range of 23 to 91 cm (9 to 36 inches).



SJE Quest® I and II

PN	Units/Carton	Description
1046396	15	SJE Quest®, 3-wire SPDT, 10m, Cable Weight Mini, bagged
1046397	8	SJE Quest®, 3-wire SPDT, 20m, Cable Weight Mini, bagged
1046398	20	SJE Quest® II, 3-wire SPDT, 15m, Cable Weight Mini, bagged
1046399	15	SJE Quest® II, 3-wire SPDT, 10m, Cable Weight Mini, bagged
1042845	25	SJE Quest® II, 5m, normally open, bagged
1042846	15	SJE Quest® II, 10m, normally open, bagged



SJE MicroMaster®

SJE MicroMaster® Pump Floats

Mechanically-activated, wide-angle pump switches provide automatic control of pumps, alarms, and control panels in wastewater and sewage applications. Adjustable pumping range of 20 to 91 cm (8 to 36 inches). Max. pump running current of 10 amps. Max. pump starting current of 60 amps.

PN	Units/Carton	Description
1046405	25	SJE MicroMaster®, 10m, Cable Weight Mini, bagged



SJE VerticalMaster® II

SJE VerticalMaster® II Pump Floats

Mechanically-activated pump switches designed to operate in sump or non-potable water applications with limited space. Adjustable pumping range of 2 to 17 cm (.75 to 6.5 inches). Max. pump running current of 10 amps. Max. pump starting current of 60 amps.

PN	Units/Carton	Description
1046403	40	SJE VerticalMaster® II, 2m, bagged
1046404	20	SJE VerticalMaster® II, 10m, bagged

SJE
Rhombus



SJE MicroMaster®



SJE MegaMaster™



Tank Alert® EZ

SJE MegaMaster® Pump Floats - CE Rated

Mechanically-activated, narrow-angle control float monitors liquid levels and activates pump control panels for municipal water and sewage applications. Internal switching mechanism has unique gold cross-point contacts for reliable control of current up to 1 amp. Large, twin wall tear drop shaped design offers increased buoyancy. 3-wire cable - SPDT (Single Pole, Double Throw) can be wired as normally open (high levels) or normally closed (low levels).

PN	Units/Carton	Description
1042842	15	SJE MegaMaster®, 5m, internally weighted, bagged
1042843	10	SJE MegaMaster®, 10m, internally weighted, bagged
1042844	6	SJE MegaMaster®, 20m, internally weighted, bagged

SJE SignalMaster® SPDT Control Floats

Mechanically-activated, narrow-angle control float monitors liquid levels and activates pump control panels for water and sewage applications. 3-wire cable - SPDT (Single Pole, Double Throw) can be wired as normally open (high levels) or normally closed (low levels). Control differential of 4 cm (1.5") above or below horizontal.

PN	Units/Carton	Description
1046400	20	SJE SignalMaster®, 3-wire SPDT, 5m, Cable Weight Mini, bagged
1046401	15	SJE SignalMaster®, 3-wire SPDT, 10m, Cable Weight Mini, bagged
1046400	8	SJE SignalMaster®, 3-wire SPDT, 20m, Cable Weight Mini, bagged

Tank Alert® EZ Alarm System - CE Rated

Innovative, 240V indoor/outdoor alarm systems warns of potentially threatening level conditions in lift pump chambers, sump pump basins, holding tanks, sewage, agricultural and other wastewater applications. The sleek, 2-color molded enclosure integrates the LED red beacon; the upper half illuminates and horn sounds in an alarm condition. Once the condition is cleared, the alarm will reset. The removable cover allows greater access for field wiring. Includes external mounting tabs for easy installation.

PN	Units/Carton	Description
1046406	24	Tank Alert® EZ, no float

